## **MY23 MAVERICK X MR TURBO RR**



## **HIGHLIGHTS**

- Smart-Lok™\* front differential
- FOX† 2.5 PODIUM QS3 Piggyback shocks
- Snorkeled engine air intake and CVT
- Belt monitoring system
- 850 W Magneto
- 7.6 in. (19.3 cm) digital display with keypad
- X-package graphics/seats
- · Can-Am LED signature
- 14 in. (35.6 cm) cast-aluminum beadlock wheels
- 30 in. (76.2 cm) ITP Cryptid tires
- Front bumper, half-doors
- Front tow hook
- 4,500-lb (2,041 kg) winch with synthetic rope
- HMWPE full skid plate

| ENGINE               |   |
|----------------------|---|
| Туре                 | 149 kW (200 hp*), Rotax® ACE (Advanced<br>Combustion Efficiency) 900 cc Turbocharged<br>Triple-cylinder engine, liquid cooled with integrated<br>intercooler, high-performance air filter and<br>strategically positioned engine air intake                     |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)  |
| Transmission         | PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L / H / N / R / P  |
| Drive Train          | Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry |
| Power Steering       | High torque Tri-Mode Dynamic Power Steering<br>(DPS™)   |
| SUSPENSIONS          |   |
| Front Suspension     | Arched double A-arm with sway bar / 22 in.<br>(55.9 cm) travel / Trophy truck inspired arms   |
| Front Shocks         | FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment  |
| Rear Suspension      | 4-link Torsional Trailing-arm X (TTX) with sway bar<br>and arched lower links / 22 in. (55.9 cm) travel   |
| Rear Shocks          | FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment and bottom-out control   |
| TIRES / WHEELS       |   |
| Front & Rear Tires   | ITP Cryptid 30 x 9 / 11 x 14 in. (76.2 x 22.9 / 27.9 x 35.6 cm)   |
| Wheels               | 14 in. (35.6 cm) cast-aluminum beadlock   |
| BRAKES               |   |
| Front                | Dual 262 mm disc brakes with hydraulic twin-<br>piston calipers   |
| Rear                 | Dual 248 mm disc brakes with hydraulic twin-<br>piston calipers   |

| DIMENSIONS | / CAPACITIES |
|------------|--------------|
|------------|--------------|

| DIIVIENSIONS / CAPACITIES | )  |
|---------------------------|--|
| Estimated Dry Weight *    | 1,758 lb (797.4 kg)                            |
| Chassis / Cage            | Dual-phase 980 steel                           |
| LxWxH                     | 132.3 x 74.2 x 68 in. (336 x 188.5 x 172.7 cm) |
| Wheelbase                 | 102 in. (259.1 cm)                             |
| Ground Clearance          | 16 in. (40.6 cm)                               |
| Rack Capacity             | 200 lb (91 kg) with LinQ™ quick-attach         |
| Storage Capacity          | Total: 2.5 gal (9.4 L)                         |
| Fuel Capacity             | 10.5 gal (40 L)                                |
|                           |  |
| FEATURES                  |  |

| Gauge           | 7.6 in. (19.3 cm) wide digital display with keypad                              |
|-----------------|---|
| Instrumentation | DC Outlet (10-A)  |
| Magneto         | 850 W   |
| Ingnition       | RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button       |
| Lighting        | LED headlights<br>LED signature<br>LED tail lights                              |
| Winch           | 4,500 lb (2,041 kg) winch with synthetic rope                                   |
| Protection      | Front bumper<br>Half-doors<br>Front and rear tow hooks<br>HMWPE full skid plate |

## WARRANTY

| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|
|                  |                             |

<sup>\*149</sup>kw/200hp based on MY22 U.S. EPA certification, or 145kw/195hp based on current EU NRMM certification.



